

FEATURES



- Wireless digital transmission of Video and Audio
- Free Input Voltage (DC 11V ~ 32V)
- Motorized shutter camera support & camera heater support
- Remote controlled pairing
- Re-pair function to enable interchanging trailers
- Signal strength indicator
- Status LEDs
- Total 4 triggers (at 4CHRX side, to activate picture per TX)
- Capacity to pair up to 4 pcs transmitter at the same time
- High quality thermoplastic urethane cables (TPU)
- IP69K waterproof (transmitters & receiver)
- Anodized aluminum housing (corrosion-proof)
- Setpackage 4CHRX-TX: 2 pcs transmitter (TX)
1 pce receiver (4CHRX)

Optional: max. 2 pcs transmitter (TX)

Specifications

General	Operating frequency	2400MHZ-2483MHZ
	Modulation system	FSK
	Signal reception area	150-200M (in open air)
	Operating temperature	-30°C ~ 80°C
	Operating current	0.13-0.17A
	IP Rating	IP69K
Transmitter (TX) (2 pcs included)	Power supply	DC 11 ~ 32V
	Power consumption	Max. 1.87 W (at DC 11V)
	Video input	CVBS 1.0VP-P, 75Ω
	Audio input	AUDIO MAX 2VP-P, 50Ω
	TPU cable length	Approx. 400cm
	Dimensions	131mm x 100mm x 25.6mm
	Weight	0.28KG
Receiver (4CHRX) (1 pce included)	Power supply	DC 11 ~ 32V
	Power consumption	Max. 1.87 W (at DC 11V)
	Video output	CVBS 1.0VP-P, 75Ω
	Audio output	AUDIO MAX 2VP-P, 50Ω
	Pixels	720 x 576
	TV system	PAL
	Frame rate	25-30 frames/sec
	TPU cable length	Approx. 600cm
	Dimensions	131mm x 100mm x 25.6mm
Weight	0.28KG	